



Description

This indicator with its wireless transmitter is a single-channel high resolution general purpose weight indicator. Housed in enhanced ABS plastic enclosure, the indicator's front panel consists of a large 6digit 7-segment display and 6-button keypad. With its easy-to-use user interface and versatile functions, it is an ideal indicator for various weighing applications, like bench scale, floor scale, check-weigher, counting scale, etc.

Features

- ◆ ABS plastic housing
- ◆ 6-digit 1.2inch/30mm high-intensity LED display
- ◆ 6-digit 1.6inch/40mm LCD display with backlight
- ◆ 6-key flat tact switch keypad
- ◆ Drives up to 8x350ohm loadcells/16x700 ohm load cells
- ◆ Built-in 6V/4.0Ah maintenance-free rechargeable battery
- ◆ Structured menu and user-friendly warning messages

Specifications

| | |
|-----------------------------|----------------------|
| Full Scale Input Signal | -3.9~+3.9mV/V |
| Loadcell Excitation Voltage | 3.30±2% VDC (typ.) |
| No. of Loadcells | 8x350Ω / 16x700Ω |
| Internal Visible Resolution | 1 000 000 counts |
| Measurement Rate | 10 measurements/s |
| Operating temperature | -10 ~ +50 deg C |
| Storage temperature | 20 ~ +60 deg C |
| Operating humidity | 0 ~ 90 % at 20 deg C |